

Revision Date: 13-Oct-2015

Revision Number: 3

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name Product Code Alternate Product Code Product Class Color Recommended use Restrictions on use

DEEP COLORS VAN DYKE BROWN RF5558

XY5321 WATER THINNED PAINT brown Paint No information available

Rosco Laboratories Inc.

52 Harbor View Avenue Stamford, CT 06902, USA Phone: (203)-708-8900 www.rosco.com

Emergency Telephone Number(s) CHEMTREC (US): 800-424-9300 CHEMTREC (outside US): (703)-527-3887

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

| Carcinogenicity | Category 1A |
|--|-------------|
| Specific target organ toxicity (repeated exposure) | Category 1 |

Label elements

Danger

Hazard statements

May cause cancer Causes damage to organs through prolonged or repeated exposure



Appearance liquid

Odor little or no odor

Precautionary Statements - Prevention

Obtain special instructions before use Do not handle until all safety precautions have been read and understood Use personal protective equipment as required Do not breathe dust/fume/mist/vapors/spray Wash face, hands and any exposed skin thoroughly after handling Do not eat, drink or smoke when using this product

Precautionary Statements - Response

If exposed or concerned get medical attention

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not Applicable

Other information

No information available

3. COMPOSITION INFORMATION ON COMPONENTS

| Chemical Name | CAS-No | Weight % (max) |
|------------------------------------|------------|----------------|
| Cristobalite | 14464-46-1 | 10 |
| Talc | 14807-96-6 | 5 |
| Diatomaceous silica, flux-calcined | 68855-54-9 | 5 |
| Iron oxide | 1309-37-1 | 5 |
| Silica, crystalline | 14808-60-7 | 0.5 |
| Carbon black | 1333-86-4 | 0.5 |

| | 4. FIRST AID MEASURES |
|------------------------------------|---|
| General Advice | No hazards which require special first aid measures. |
| Eye Contact | Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician. |
| Skin Contact | Wash off immediately with soap and plenty of water removing all contaminated clothes and shoes. |
| Inhalation | Move to fresh air. If symptoms persist, call a physician. |
| Ingestion | Clean mouth with water and afterwards drink plenty of water. Consult a physician if necessary. |
| Most Important Symptoms/Effects | None known. |
| Notes To Physician | Treat symptomatically. |

| 5. FIRE-FIGHTING MEASURES | |
|--|--|
| Suitable Extinguishing Media | Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. |
| Protective Equipment And Precautions For Firefighters | As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. |
| Specific Hazards Arising From The Chemical | Closed containers may rupture if exposed to fire or extreme heat. |
| Sensitivity To Mechanical Impact | No |
| Sensitivity To Static Discharge | No |
| Flash Point Data Flash Point (°F) Flash Point (°C) Flash Point Method | Not applicable Not applicable Not applicable |
| Flammability Limits In Air | |
| Lower Explosion Limit Upper Explosion Limit | Not applicable Not applicable |
| NFPA Health: 1 Flammability: 0 Ins | tability: 0 Special: Not Applicable |

NFPA Legend

- 0 Not Hazardous
- 1 Slightly
- 2 Moderate
- 3 High
- 4 Severe

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

| 6. | ACCIDENTAL RELEASE MEASURES |
|---------------------------|---|
| Personal Precautions | Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. |
| Other Information | Prevent further leakage or spillage if safe to do so. |
| Environmental Precautions | See Section 12 for additional Ecological Information. |
| Methods For Clean-Up | Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal. |
| | |

7. HANDLING AND STORAGE

Handling Avoid contact with skin, eyes and clothing. Avoid breathing vapors, spray mists or sanding dust. In case of insufficient ventilation, wear suitable respiratory equipment.

Storage

Keep container tightly closed. Keep out of the reach of children.

Incompatible Materials

No information available

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limits

| Chemical Name | ACGIH | OSHA |
|---------------------|-----------------------------|--|
| Cristobalite | 0.025 mg/m³ - TWA | respirable - (1/2)(10)/(%SiO2 + 2) mg/m ³ TWA respirable - (1/2)(250)/(%SiO2 + 5) mppcf TWA total dust - (1/2)(30)/(%SiO2 + 2) mg/m ³ TWA |
| Talc | 2 mg/m³ - TWA | 20 mppcf - TWA |
| Iron oxide | 5 mg/m³ - TWA | 10 mg/m ³ - TWA |
| Silica, crystalline | 0.025 mg/m³ - TWA | respirable - (10)/(%SiO2 + 2) mg/m ³ TWA respirable - (250)/(%SiO2 + 5) mppcf TWA total dust - (30)/(%SiO2 + 2) mg/m ³ TWA |
| Carbon black | 3.5 mg/m ³ - TWA | 3.5 mg/m ³ - TWA |

Legend

ACGIH - American Conference of Governmental Industrial Hygienists Exposure Limits OSHA - Occupational Safety & Health Administration Exposure Limits N/E - Not Established

| Engineering Measures | Ensure adequate ventilation, especially in confined areas. |
|---|---|
| Personal Protective Equipment Eye/Face Protection Skin Protection Respiratory Protection | Safety glasses with side-shields. Protective gloves and impervious clothing. In case of insufficient ventilation wear suitable respiratory equipment. |
| Hygiene Measures | Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash thoroughly after handling. |

9. PHYSICAL AND CHEMICAL PROPERTIES

| Appearance Odor Odor Threshold Density (lbs/gal) Specific Gravity pH Viscosity (cps) Solubility Water Solubility Evaporation Rate Vapor Pressure | liquid little or no odor No information available 9.6 - 9.9 1.15 - 1.19 No information available No information available No information available No information available No information available |
|--|---|
| Vapor Pressure Vapor Density | No information available |
| | |

| Wt. % Solids Vol. % Solids | 30 - 40 20 - 30 |
|---|--------------------------|
| Wt. % Volatiles | 60 - 70 |
| Vol. % Volatiles | 70 - 80 |
| VOC Regulatory Limit (g/L) | < 50 |
| Boiling Point (°F) | 212 |
| Boiling Point (°C) | 100 |
| Freezing Point (°F) | 32 |
| Freezing Point (°C) | 0 |
| Flash Point (°F) | Not applicable |
| Flash Point (°C) | Not applicable |
| Flash Point Method | Not applicable |
| Flammability (solid, gas) | Not applicable |
| Upper Explosion Limit | Not applicable |
| Lower Explosion Limit | Not applicable |
| Autoignition Temperature (°F) | No information available |
| Autoignition Temperature (°C) | No information available |
| Decomposition Temperature (°F) | No information available |
| Decomposition Temperature (°C) | No information available |
| Partition Coefficient (n-octanol/water) | No information available |

10. STABILITY AND REACTIVITY

| Reactivity | Not Applicable |
|------------------------------------|--|
| Chemical Stability | Stable under normal conditions. |
| Conditions To Avoid | Prevent from freezing. |
| Incompatible Materials | No materials to be especially mentioned. |
| Hazardous Decomposition Products | None under normal use. |
| Possibility Of Hazardous Reactions | None under normal conditions of use. |

11. TOXICOLOGICAL INFORMATION

| Product Information | | |
|--|---|--|
| Information on likely routes of exposure | | |
| Principal Routes of Exposure | Eye contact, skin contact and inhalation. | |
| Acute Toxicity | | |
| Product Information | No information available | |
| Information on toxicological effects | | |
| Symptoms | No information available | |
| Delayed and immediate effects as well as chronic effects from short and long-term exposure | | |
| Eye contact | May cause slight irritation. | |
| | | |

| Skin contact | Substance may cause slight skin irritation. Prolonged or repeated contact may dry skin and cause irritation. |
|--|--|
| Inhalation | May cause irritation of respiratory tract. |
| Ingestion | Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. |
| Sensitization: | No information available |
| Neurological Effects | No information available. |
| Mutagenic Effects | No information available. |
| Reproductive Effects | No information available. |
| Developmental Effects | No information available. |
| Target Organ Effects | No information available. |
| STOT - single exposure | No information available. |
| STOT - repeated exposure | Causes damage to organs through prolonged or repeated exposure if inhaled. Contains: Crystalline Silica which has been determined to be carcinogenic to humans by IARC (1) when in respirable form. Risk of cancer depends on duration and level of inhalation exposure to spray mist or dust from sanding the dried paint. |
| Other adverse effects Aspiration Hazard | No information available. No information available |

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 774313 mg/kg

Component

Acute Toxicity

Iron oxide LD50 Oral: > 5000 mg/kg (Rat) vendor data <u>Silica, crystalline</u> LD50 Oral: 500 mg/kg (Rat) vendor data <u>Carbon black</u> LD50 Oral: > 15400 mg/kg (Rat) LD50 Dermal: > 3000 mg/kg (Rabbit)

Carcinogenicity

The information below indicates whether each agency has listed any ingredient as a carcinogen:.

| Chemical Name | IARC | NTP | OSHA Carcinogen |
|---------------------|----------------------|-------------|-----------------|
| | 1 - Human Carcinogen | | Listed |
| Cristobalite | | | |
| | 1 - Human Carcinogen | Known Human | Listed |
| Silica, crystalline | | Carcinogen | |
| | 2B - Possible Human | | Listed |
| Carbon black | Carcinogen | | |

• Crystalline Silica has been determined to be carcinogenic to humans by IARC (1) when in respirable form. Risk of cancer depends on duration and level of inhalation exposure to spray mist or dust from sanding the dried paint.

Legend

IARC - International Agency for Research on Cancer NTP - National Toxicity Program OSHA - Occupational Safety & Health Administration

12. ECOLOGICAL INFORMATION

Ecotoxicity Effects

The environmental impact of this product has not been fully investigated.

Product Information

Acute Toxicity to Fish No information available

Acute Toxicity to Aquatic Invertebrates

No information available

<u>Acute Toxicity to Aquatic Plants</u> No information available

Persistence / Degradability

No information available.

Bioaccumulation / Accumulation

No information available.

Mobility in Environmental Media

No information available.

Ozone

No information available

Component

Acute Toxicity to Fish

No information available

Acute Toxicity to Aquatic Invertebrates

No information available

Acute Toxicity to Aquatic Plants

No information available

| 13. DISPOSAL CONSIDERATIONS | | |
|-----------------------------|---|--|
| Waste Disposal Method | Dispose of in accordance with federal, state, provincial, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options. | |
| | 14. TRANSPORT INFORMATION | |
| DOT | Not regulated | |
| ICAO / IATA | Not regulated | |
| IMDG / IMO | Not regulated | |

15. REGULATORY INFORMATION

International Inventories

| TSCA: United States | Yes - All components are listed or exempt. |
|---------------------|--|
| DSL: Canada | Yes - All components are listed or exempt. |

Federal Regulations

SARA 311/312 hazardous categorization

| Acute Health Hazard | No |
|-----------------------------------|-----|
| Chronic Health Hazard | Yes |
| Fire Hazard | No |
| Sudden Release of Pressure Hazard | No |
| Reactive Hazard | No |

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

None

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following HAPs:

None

State Regulations

California Proposition 65

This product may contain small amounts of materials known to the state of California to cause cancer or reproductive harm.

State Right-to-Know

| Chemical Name | Massachusetts | New Jersey | Pennsylvania |
|------------------------------------|---------------|------------|--------------|
| Cristobalite | Х | X | Х |
| Talc | Х | X | Х |
| Diatomaceous silica, flux-calcined | | | Х |
| Iron oxide | Х | X | Х |
| Silica, crystalline | Х | Х | Х |
| Carbon black | Х | X | Х |

Legend

X - Listed

16. OTHER INFORMATION

HMIS

- Health: 1* Flammability: 0
- Reactivity: 0

PPE: -

HMIS Legend

- 0 Minimal Hazard
- 1 Slight Hazard
- 2 Moderate Hazard
- 3 Serious Hazard
- 4 Severe Hazard
- * Chronic Hazard

X - Consult your supervisor or S.O.P. for "Special" handling instructions.

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

| Prepared By | Product Stewardship Department Rosco Laboratories Inc. 52 Harbor View Avenue Stamford, CT 06902, USA Phone: (203)-708-8900 |
|------------------|--|
| Revision Date: | 13-Oct-2015 |
| Revision Summary | Not available |

Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

END OF SAFETY DATA SHEET