
OPTI-SCULPT™


Engineered For Precise Beam Sculpting





Rosco OPTI-SCULPT filters provide precise angular beam control – enabling lighting professionals to accurately and affordably control the shape of their light. Rosco's unique, proprietary process offers increased brightness with engineered light distribution that has been laboratory tested for accuracy and repeatability.

OPTI-SCULPT filters are currently available in eleven different symmetrical and asymmetrical patterns, including the unique 40°/60° Reversible pattern. The filters are manufactured using flame-retardant, 10 mil thick, semi-rigid polycarbonate, and they are available in 20"x24" & 40" x 24" (50 cm x 60 cm & 100 cm x 60 cm) seamless sheets that can be cut to any size and shape to fit any light fixture.









KEY FEATURES

- Engineered and laboratory tested for accurate and repeatable beam shaping
- High transmission vs standard diffusion materials
- Available in 20"x24" and 40"x24" SEAMLESS sheets
- Manufactured using heat-resistant, flame-retardant polycarbonate
- Designed for LED fixtures, but also suitable for use on conventional fixtures
- Durable The filter's performance is not adversely affected by dust or fingerprints
- Available in eleven different patterns, including the unique, reversible 40°/60°

OPTI-SCULPT™

Engineered For Precise Beam Sculpting



SPECIFICATIONS

Thickness: 10 mil (254µ) Installation: Each OPTI-SCULPT Filter has a textured

Substrate: Substrate:

Contains flame retardant additive

Contains UV inhibitors

In order to achieve the filter's stated beam shape, position the OPTI-SCULPT

ntains UV inhibitors filter with the smooth side towards the

Available Sizes: 20" x 24" (50 cm x 60 cm) sheet – seamless lamp. For the 40°/60° Reversible OPTI-SCULPT Filter – position the filter

40" x 24" (100 cm x 60cm) sheet – seamless

OPTI-SCULPT Filter – position the filter with the smooth side towards the lamp to achieve the 40° beam shape and the

Thermal Performance: $-40^{\circ} \, \text{F} - +320^{\circ} \, \text{F} \, (-40^{\circ} \, \text{C} - +160^{\circ} \, \text{C})$ achieve the 40° beam shape and the textured side of the filter toward the lamp

to achieve the 60° beam shape.

Flame Retardant Rating: M1, B1, C1, BS3944 PART 1 1992, NFPA 701 Patent Pending

OPTI-SCULPT™	
Item Code	Description
108100102420	OPTI-SCULPT Filter, 10° - 20" x 24" sheet
108100102440	OPTI-SCULPT Filter, 10° - 40" x 24" sheet
108100202420	OPTI-SCULPT Filter, 20° - 20" x 24" sheet
108100202440	OPTI-SCULPT Filter, 20° - 40" x 24" sheet
108100302420	OPTI-SCULPT Filter, 30° - 20" x 24" sheet
108100302440	OPTI-SCULPT Filter, 30° - 40" x 24" sheet
10840R602420	OPTI-SCULPT Filter, 40%60° Reversible - 20" x 24" sheet
10840R602440	OPTI-SCULPT Filter, 40%60° Reversible - 40" x 24" sheet
108110202420	OPTI-SCULPT Filter, 10°x20° - 20" x 24" sheet
108110202440	OPTI-SCULPT Filter, 10°x20° - 40" x 24" sheet
108110302420	OPTI-SCULPT Filter, 10°x30° - 20" x 24" sheet
108110302440	OPTI-SCULPT Filter, 10°x30° - 40" x 24" sheet
108110402420	OPTI-SCULPT Filter, 10°x40° - 20" x 24" sheet
108110402440	OPTI-SCULPT Filter, 10°x40° - 40" x 24" sheet
108110602420	OPTI-SCULPT Filter, 10°x60° - 20" x 24" sheet
108110602440	OPTI-SCULPT Filter, 10°x60° - 40" x 24" sheet
108115352420	OPTI-SCULPT Filter, 15°x35° - 20" x 24" sheet
108115352440	OPTI-SCULPT Filter, 15°x35° - 40" x 24" sheet
108115452420	OPTI-SCULPT Filter, 15°x45° - 20" x 24" sheet
108115452440	OPTI-SCULPT Filter, 15°x45° - 40" x 24" sheet
108120402420	OPTI-SCULPT Filter, 20°x40° - 20" x 24" sheet
108120402440	OPTI-SCULPT Filter, 20°x40° - 40" x 24" sheet

OPTI-SCULPT™

Beam Patterns



