

# Performance Floor

This durable all-purpose floor is best used for permanent installations in studios, multi-purpose rooms and showrooms. Performance Floor's sound absorption, durability and abrasion resistance allows it to stand up wherever traffic is heaviest.

## Composition:

Polyvinyl chloride resin, plasticizers and pigments

## Nominal thickness:

0.100" (2.5mm)

Co-Calendared wear layer: 0.032" (0.08 mm)

Middle and backing layers: 0.068" (1.7 mm)

## Roll Size:

72" x 60' (1.830 mm x 18.28 m)

## Weight:

5 lbs per linear foot (2.27 kg per linear foot)

300 lbs per roll (136.08 kg per roll)

## Colors Available:

Black, Dark Grey, Light Grey and White

## Flame Spread:

ASTM E684-97 Class 1 per NFPA 253

## Smoke Density:

ASTM E662/NFPA 258

## Abrasion Resistance:

ASTM D3884—Net weight loss after 1000 revolutions: 0.04%

## Static Load Limit:

ASTM F970-87—Residual compression after exposure to a load of 125 lbs/24 hours-.004"

## Flexibility:

ASTM F137—Passes

## Floor Speed:

Medium-slow

## Product Numbers

300 73035 7200 - Black 6'-0" x 60' (1.83 m x 18.29 m)

300 73031 7200 - Light Grey 6'-0" x 60' (1.83m x 18.29 m)

300 73025 7200 - Dark Grey 6'-0" x 60' (1.83 m x 18.29 m)

300 73030 7200 - White 6'-0" x 60' (1.83 m x 18.29 m)