

Custom LitePad[®] CCT 95

Low profile tunable white light emitting LED panel for backlight or area lighting, available in standard or custom sizes and LED configurations with tunable white light that from 2700K to 6500K, and dimming and control accessories.

General

1. The luminaire shall be a flat panel LED light with two channels of LEDs for tunable white from 2700K to 6500K and dimming and control accessories. The luminaire shall be a Rosco LitePad CCT with dimming and control accessories as manufactured by Rosco Labs, Inc.
2. The luminaire shall be available in standard or custom sizes from a minimum of 2 in x 2 in (50 mm x 50 mm) to maximum of 59 in x 118 in (1.5 m x 3 m), with center cutouts possible up to 1.5 inch from the edge of the luminaire.
3. The luminaire shall be powered and controlled with Rosco 12 VDC or 24 VDC power supply, leads, and controls.
4. The luminaire shall be UL Listed (File E350056) for low voltage lighting products.

Physical

5. The luminaire shall be constructed of a cast optical grade acrylic panel with light guiding channels etched into the rear surface and, LEDs populated along one or multiple edges, along with a heat sink and an opaque white backing. The overall luminaire panel shall be no more than 0.32 in (8 mm) thick and the weight no more than 2 lbs (900 g) per ft².
6. Size of the luminaire shall be customizable for the design or installation being specified, from a minimum of 2 in x 2 in (50 mm x 50 mm) to maximum of 59 in x 118 in (1.5 m x 3 m), with center cutouts possible up to 4 inches (102 mm) from the edge of the luminaire.
7. Placement of lead wire exit shall be corner, notched corner, side or rear of panel.
8. The power supply shall accept 90-264VAC input and shall provide 12 VDC or 24 VDC output.
9. The following shall be included:
 - a. Luminaire
 - b. 12 VDC or 24 VDC Power supply and controller
 - c. 3 core, 20 AWG wire, 4-ft (1.2 m) length, unterminated

Optical

10. LEDs shall be configurable on long edges, short edges, all 4 sides, by inside or outside circumference, or in a custom configuration.
11. Color temperature option shall be tunable color temperature from 2700K to 6500K.

Environmental and Agency Compliance

12. The luminaire shall be UL Listed for low voltage lighting products.
13. The luminaire shall be rated at IP61 for Indoor use.

Custom LitePad® CCT 95

Thermal

14. Luminaire shall operate in an ambient temperature range of -22° F min to 104° F max (-30° C min to 40° C max)

Electrical

- 15. The luminaire shall be equipped with an external 12 VDC or 24 VDC power supply, dimming controls compatible with 12 VDC or 24 VDC power supplies shall be offered for customizable installations.
- 16. Lead cable from power supply to luminaire and between luminaires shall be a 3 core, 20 AWG wire with 2.1 mm x 5.5 mm barrel connector with two connections for color temperature control and one for a common ground.
- 17. Luminaire shall consume 3.6w per linear ft of LED.
- 18. The luminaires shall be wired together in parallel.

LED Emitters

- 19. The luminaire shall use .25 watt surface mount diodes.
- 20. The color temperature shall be 2700K for 50% of the LEDs and 6500K for 50% of the LEDs.

Control and Dimming

21. The luminaire shall be dimmed by 0-10V, DMX or DALI dimming devices compatible with ELV power supplies.

Specification Ordering Example

Below is the specification ordering form as it appears on the data sheet available from the Resource Center at: <http://www.rosco.com/resource-center>

SPECIFICATION ORDERING INFORMATION

CCT 95	Color Temperature	Size	LED Placement
	LitePad CCT 95 - 2700K to 6500K tunable	Length x Width (inches/mm) Diameter CS - Custom Shape (drawing may be required)	L1 - 1 Long Edge L2 - 2 Long Edges S1 - 1 Short Edge S2 - 2 Short Edges A4 - All 4 Sides DIA - Circumference CI - Custom Illumination

CCT 95 - 12 in x 12 in - A4 specifies a 12 in square LitePad CCT with LEDs on all sides.
CCT 95 - 200 mm - DIA inside specifies a 200 mm round LitePad CCT with LEDs on the inside circumference.

When ordering custom shapes (**CS**) or custom illuminations (**CI**), be sure to include a drawing and verbal description of the desired shape and distribution.

If there are questions, contact: customlitepad@rosco.com

Table Specification for Custom LitePad® CCT 95

Type ID	Qty	Description	Manufacturer	Alternate Manufacturer	Light Source / Power Source			Control
					Color Temp.	LED Type	Watts/Volts	
		Flat panel LED at .3 in (8 mm) thickness, made of cast acrylic that holds indirect LED sources, and is powered with 12 VDC or 24 VDC power supply and 3 core, 20 AWG wire with 2.1 mm x 5 mm barrel. Size: _____	Rosco Labs		Tunable 2700K to 6500K	.25 watt surface mounted diode, positioned: Long Edge Long Edges Short Edge Short Edges All 4 Sides Circumference Custom	3.6w per ft. for _____ total watts 12 VDC or 24 VDC	Luminaire to be controlled with power supply accessory, part number:
Comments								